

HYMAX® 2 FLIP GASKET

Wide-Range Coupling with No-Tear Gasket




















Flip Gasket

EPDM compounded for water and sewage, meets NSF 61 and NSF 372 standards for contact with drinking water



Spherical Spacers

AISI 304 or 316 Stainless Steel

End Ring

ASTM A283/A283M Grade C Steel

Coating

100% fusion bonded epoxy for enhanced corrosion protection. Average thickness 14 mm, meets NSF 61 and NSF 372 standards

Center Ring

ASTM A53 Grade A Steel

HYMAX® 2 PRODUCT PORTFOLIO



HYMAX 2 WIDE RANGE COUPLING

Nominal pipe size 1.5" - 12"



HYMAX 2 FLANGE ADAPTOR & FA LONG BODY

Nominal pipe size 1.5'' - 12''



HYMAX 2 LONG BODY

Nominal pipe size 1.5" - 12"



HYMAX 2 REDUCER

Nominal pipe size 1.5" - 12"



HYMAX 2 THREADED OUTLET

Nominal pipe size 1.5" - 12"



FLANGED OUTLET

Nominal pipe size 4'' - 12''



HYMAX 2 ELBOWS

Nominal pipe size 2" - 12"



HYMAX 2 CATHODIC

Nominal pipe size 2'' - 12''



HYMAX END CAP

Nominal pipe size 4'' - 12''Removable
gasket only



HYMAX 2 FLANGE ADAPTOR WITH NPT

Nominal pipe size 3'' - 12''

THE HYMAX 2 FAMILY FEATURES



FAST AND EASY INSTALLATION

- Lightweight construction enables fast and easy installation, with minimum manpower, reducing time in the ditch and improving worker safety.
- Unique top-facing bolts enable easy installation access.
- Ready-to-use, stab-on design eliminates the need for extensive under-pipe digging and work.



MULTIPLE APPLICATIONS

- All products accommodate a variety of pipe materials: ductile iron, cast iron, steel, copper, PE, PVC, AC and GRP.
- One single product can connect pipes of two different materials, allowing transition capability of up to 1.3".



FLEXIBLE CONNECTION

- Allows for up to 4° angular deflection on each end, during installation as well as for misaligned pipes.
- Absorbs post-installation dynamic pipe deflection of up to 4° on each end, reducing the risk of damage and cracking due to ground shifts and temperature changes.
- Adapts to out-of-round pipe shape (up to 0.31"), for optimum fit on both ends.



HIGH DURABILITY

- High-quality sealing solution patented hydraulically-assisted gasket features two-stage sealing: mechanical sealing that is effective under vacuum or non-pressure; and selfinflated gasket using water pressure.
- Fusion-bonded epoxy coating enables an insulated product and prevents corrosion.
- Nuts, bolts and other components are made of stainless steel.
- Innovative radial closing design and sealing systems eliminate installation errors.
- Advanced molecular anti-galling (MAG) on nuts and bolts, prevents galling and enables repeated bolt tightening; it also eliminates the need for grease, preventing dust and dirt build-up.
- One-piece design delivers fortified strength and enhanced flexibility.



COST-SAVING

- HYMAX 2 products suit a wide range of pipe diameters, replacing the need to use dedicated products and thus reducing inventory costs and saving shelf space.
- Fast and easy installation saves time and money.

ADDRESSING THE COMPLETE RANGE OF PIPE TYPES



HYMAX 2 IS BASED ON THE ORIGINAL GAME-CHANGING HYMAX THAT HAS BEEN FIELD-PROVEN IN MILLIONS OF INSTALLATIONS IN THE US.

- HYMAX 2's patented flip gasket can be easily flipped in or out to accommodate different pipe OD's
- Advanced no-tear gasket technology for maximum installation efficiency
- Only 2 top-facing bolts for faster, easier, safer installation
- Dynamic deflection of 4° per side reducing future pipe damage
- Suitable for all types of pipes ductile iron, cast iron, steel, copper, PE, PVC, AC, GRP

About HYMAX®

HYMAX, a Mueller brand, develops, designs, and manufactures market-leading products for repairing and connecting different types of pipes for both potable water and sewage. In more than 160 years of combined industry leadership with Mueller, and millions of installations worldwide, HYMAX has earned solid reputations for providing innovative, high-quality products, that meet installers' field needs.

HYMAX offers a full line of solutions, including standard products that range from 1.5″ to 85″ and custom-made products according to customers' requirements. The wide-range coupling introduced unprecedented ease of use, with a radial closing mechanism of only 2 - 4 top-facing bolts, enabling faster and safer installation.

Our company is built by industry experts with extensive field experience. Therefore, we can better understand the challenges of the installer and provide real solutions. The HYMAX product line saves costs by reducing inventory and providing long lasting value. Offering extreme durability and outstanding connection flexibility, these products prevent future pipe damage, delivering long-lasting value.

For more information about us or to view our full line of water products, please visit HymaxUSA.com or call HYMAX customer service at 855.457.2879.

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller® Echologics® Hydro Gate® Hydro-Guard® HYMAX® Krausz® Jones® Mi Net® Milliken® Pratt® Pratt Industrial® Singer® and ILS Pine Valve & Hydrant Please see mueller on com/brands to learn more

© 2021 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Co., LLC., its affiliates or other third parties. Products above marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).

